Inteligentna Elektronika
Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90
E-mail: info@centrumprojekcji.pl



Nazwa	**Coronis Fusion 6MP LED MDCC-6330**
Cena	**0,00 zł**
Producent	**Barco**

OPIS PRODUKTU

Screen technology
TFT AM Color LCD Dual Domain IPS-Pro
Active screen size (diagonal)
772 mm (30.4")
Active screen size (H x V)
654 x 409 mm (25.8 x 16.1")
Aspect ratio (H:V)
16:10
Resolution
Native 6MP (3280 x 2048)
Configurable to 2 x 3MP+ (1640 X 2048)
Configurable to 2 x 3MP (1536 X 2048)
Pixel pitch
0.1995 mm
Color imaging
Yes
Gray imaging
Yes
Color support
30 bit
Viewing angle (H, V)
178°
Uniform Luminance Technology (ULT)
Yes
Per Pixel Uniformity (PPU-LED)
Yes (color PPU)
Ambient Light Compensation (ALC)

Yes
Backlight Output Stabilization (BLOS)
Yes (2x)
I-Guard
Yes
Maximum luminance
720 cd/m²
DICOM calibrated luminance (ULT off)
500 cd/m²
Contrast ratio (dark reading room, typical)
1000:1 (panel typical)
Response time (Tr + Tf)
18 ms
Housing color
Black / silver
Video input signals
DVI-D Dual Link (2x), DisplayPort (2x)
Video inout terminals
NA
USB ports
1 upstream (endpoint), 3 downstream
USB standard
2.0
Power requirements (nominal)
100-240V
Power consumption (nominal)
100W
Power save mode
Yes (less than 0.5W)
Power management
DVI-DMPM, DP-DMPM
OSD languages
English, German, French, Dutch, Spanish, Italian, Portuguese, Polish, Russian, Swedish, Chinese (simplified), Japanese, Korean, Arabic
Dimensions with stand (W x H x D)
Portrait: NA
Landscape: 730 x 580~675 x 261 mm
Dimensions w/o stand (W x H x D)
Portrait: NA
Landscape: 730 x 485 x 125 mm
Dimensions packaged (W x H x D)
860 x 760 x 390 mm
Net weight with stand
20.5 kg
Net weight w/o stand
14 kg
Net weight packaged with stand
29.5 kg
Net weight packaged w/o stand
NA
Height adjustment range
96 mm
Tilt
-5° / +25°
Swivel

-30° / +30°
Pivot
NA
Mounting standard
VESA (100 mm)
Screen protection
Protective, non-reflective glass cover
Recommended modalities
CT, MR, US, DR, CR, NM, PET
Certifications
CE0120 (MDD 93/42/EEC; A1:2007/47/EC class IIb product), CE - 2004/108/EC, IEC 60950-1:2005 + A1:2009, EN 60950-1:2006 + A1:2010 + A11:2009 + A12:2011 + A2:2013, IEC 60601-1:2005, ANSI/AAMI ES 60601-1:2005 + C1:2009 + A2:2010, CAN/CSA C22.2 No. 60601-1 (2008), EN 60601-1:2006 + A11:2011, EN 60601-1-2:2007, CCC - GB9254-2008 + GB4943.1-2011 + GB17625.1-2012, KCC, VCCI, FCC class B, ICES-001 Level B, FDA 510(k), RoHS
Supplied accessories
User Guide
Quick Install Sheet
Documentation CD
System CD
Video cables (2 x DVI Dual Link, 2 x DisplayPort)
Mains cables (UK, European (CEBEC/KEMA), USA (UL/CSA; adaptor plug NEMA 5-15P), Chinese (CCC))
USB 2.0 cable
External power supply
Optional accessories
Graphics board
QA software
MediCal QAWeb
Units per pallet
NA
Pallet dimensions (W x H)
NA
Warranty
5 years
Operating temperature
0°C to 35°C (15°C to 30°C within specs)
Storage temperature
-20°C to 60°C
Operating humidity
8% - 80% (non-condensing)
Storage humidity
5% - 93% (non-condensing)
Operating altitude
3000 m