

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



BARCO

Nazwa **Coronis Fusion 6MP LED MDCC-6330**

Cena **0,00 zł**

Producent **Barco**

OPIS PRODUKTU

Screen technology

TFT AM Color LCD Dual Domain IPS-Pro

Active screen size (diagonal)

772 mm (30.4")

Active screen size (H x V)

654 x 409 mm (25.8 x 16.1")

Aspect ratio (H:V)

16:10

Resolution

Native 6MP (3280 x 2048)

Configurable to 2 x 3MP+ (1640 X 2048)

Configurable to 2 x 3MP (1536 X 2048)

Pixel pitch

0.1995 mm

Color imaging

Yes

Gray imaging

Yes

Color support

30 bit

Viewing angle (H, V)

178°

Uniform Luminance Technology (ULT)

Yes

Per Pixel Uniformity (PPU-LED)

Yes (color PPU)

Ambient Light Compensation (ALC)

Yes
Backlight Output Stabilization (BLOS)
Yes (2x)
I-Guard
Yes
Maximum luminance
720 cd/m²
DICOM calibrated luminance (ULT off)
500 cd/m²
Contrast ratio (dark reading room, typical)
1000:1 (panel typical)
Response time (Tr + Tf)
18 ms
Housing color
Black / silver
Video input signals
DVI-D Dual Link (2x), DisplayPort (2x)
Video in/out terminals
NA
USB ports
1 upstream (endpoint), 3 downstream
USB standard
2.0
Power requirements (nominal)
100-240V
Power consumption (nominal)
100W
Power save mode
Yes (less than 0.5W)
Power management
DVI-DMPM, DP-DMPM
OSD languages
English, German, French, Dutch, Spanish, Italian, Portuguese, Polish, Russian, Swedish, Chinese (simplified), Japanese, Korean, Arabic
Dimensions with stand (W x H x D)
Portrait: NA
Landscape: 730 x 580~675 x 261 mm
Dimensions w/o stand (W x H x D)
Portrait: NA
Landscape: 730 x 485 x 125 mm
Dimensions packaged (W x H x D)
860 x 760 x 390 mm
Net weight with stand
20.5 kg
Net weight w/o stand
14 kg
Net weight packaged with stand
29.5 kg
Net weight packaged w/o stand
NA
Height adjustment range
96 mm
Tilt
-5° / +25°
Swivel

-30° / +30°

Pivot

NA

Mounting standard

VESA (100 mm)

Screen protection

Protective, non-reflective glass cover

Recommended modalities

CT, MR, US, DR, CR, NM, PET

Certifications

CE0120 (MDD 93/42/EEC; A1:2007/47/EC class IIb product), CE - 2004/108/EC, IEC 60950-1:2005 + A1:2009, EN 60950-1:2006 + A1:2010 + A11:2009 + A12:2011 + A2:2013, IEC 60601-1:2005, ANSI/AAMI ES 60601-1:2005 + C1:2009 + A2:2010, CAN/CSA C22.2 No. 60601-1 (2008), EN 60601-1:2006 + A11:2011, EN 60601-1-2:2007, CCC - GB9254-2008 + GB4943.1-2011 + GB17625.1-2012, KCC, VCCI, FCC class B, ICES-001 Level B, FDA 510(k), RoHS

Supplied accessories

User Guide

Quick Install Sheet

Documentation CD

System CD

Video cables (2 x DVI Dual Link, 2 x DisplayPort)

Mains cables (UK, European (CEBEC/KEMA), USA (UL/CSA; adaptor plug NEMA 5-15P), Chinese (CCC))

USB 2.0 cable

External power supply

Optional accessories

Graphics board

QA software

MediCal QAWeb

Units per pallet

NA

Pallet dimensions (W x H)

NA

Warranty

5 years

Operating temperature

0°C to 35°C (15°C to 30°C within specs)

Storage temperature

-20°C to 60°C

Operating humidity

8% - 80% (non-condensing)

Storage humidity

5% - 93% (non-condensing)

Operating altitude

3000 m