
Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa	Projektor JVC DLA-VS4010NLG
-------	------------------------------------

Cena	0,00 zł
------	----------------

Producent	JVC
-----------	------------

OPIS PRODUKTU

Image Device

3 D-ILA® devices (1.27 inches diagonal)

4096 x 2400,

6.8um Pixel Pitch

0.25um Pixel Gap

>93% Aperture Ratio

Brightness

6000 ANSI Lumens

Display Resolution

4096 x 2400 Pixels (17:10 Aspect Ratio)

Contrast Ratio

Greater than 10,000:1 (Sequential)

Uniformity

Greater than 85%

DVI Input - Supported Resolutions

4096x2400, 4096x2160, 3840x2400, 3840x2160

2048x1200, 2400x1080, 1920x1080, 1920x1200

1600x1200, 1280x1024, 1024x768, 800x600, 640x480

DVI Clock

165MHz (single link), 330MHZ (dual link)

Latency

<10ms in 4-stripe mode

Color Bit Depth

8 bits maximum single link DVI

12 bits maximum dual link DVI

I/O Terminals

DVI-D (dual link) x 4

Ethernet, RJ45 x 1

USB, Type B (slave) x 1

RS-232C, D-Sub 9 pin (male) x 3

Remote Control

Integrated Web Browser Interface

RS-232C Fully featured control protocol

Projection Lens (optional)

GLMS4011SG - 1.1:1 Fixed lens, $\pm 25\%$ V offset

GLMS4015SZG - 1.5-1.84:1 Zoom lens, $\pm 50\%$ V and $\pm 25\%$ H offset

GLMS4021SZG - 2.15-3.65:1 Zoom lens,±50% V and ±25% H offset

Light source

Blu-Escent Laser-Excited Phosphor

2-Step Power Control (2 customizable modes)

Adjustable Power 20%-100% (88 steps)

Auto Intensity mode capable

Light Source Life

Average 20,000hrs at 100% output

Power Requirement

AC 100V-120V, 200V-240V, 50/60Hz (single phase)

Power Consumption

1250 Watts Maximum, 11.5A/5.75A, AC 110V/240V

Noise Level (0-26°C, 32- 52.3dB (A) at 39.4"/1m (3.3ft)

Operating Altitude

<6600ft (2000m) for safe operation

<4900ft (1500m) for guaranteed performance

Installation Orientation

Vertical ±90

Airflow Requirements

106cfm (3m3) per minute minimum

Dimensions (W x H x D)

26.0" x 13.5" x 36.8" (660 x 342 x 934 mm)

Weight

162lbs/73.5kg, Without Lens

Supplied Accessories

Power Cord

*Instruction manual is available from the JVC site

Approvals

CSA C22.2 No.60950-1-07/ UL60950-1 2nd

IEC60950-1/EN60950-1 2nd (EU)

EMC - FCC PART 15 SUBPART B, SECTION 15.109 CLASS A, ICES-003 Issue

5:2012 CLASS A, EN55032 2009 CLASS A, EN61000-3-2 2014, EN61000-3-3,

2013, EN55103-2 2014 E4 (EU)

Warranty

One-Year Parts and Labor (per JVC Limited Warranty)